


Soft seated butterfly valve

flu-con SERIES 24



Company profile

Airpower in Dattenberg near Linz am Rhein, located between Bonn and Koblenz, is your independent partner for pneumatic and electric rotary actuators as well as industrial valves designed for the process industry and plant construction.

The company headquarters were part of an investment, made in 2019, with a new 5000 sqm building complex comprising spacious administration, storage, and production areas.



As an independent company, we offer comprehensive and professional technical advice and support in matters of engineering and customer service. Our technical support is geared towards specific project-related requirements targeting optimal cost-benefit ratio. We attach great importance to personal contact. We are committed to support you! An experienced team ensures your absolute satisfaction. Well-engineered product technology, designed and produced according to international standards and norms, guarantees absolute safety.



We have international approvals according to DIN EN ISO 9001-2015, ATEX, SIL3, EAC etc. Our employees, either in Sales, Construction, Purchase or Assembly make sure that orders are processed smoothly and quickly. We deliver over 10.000 pneumatic actuators from 4 to 13.000 Nm from stock. Our program includes manually operated and fully automated industrial valves from nominal width DN10 to DN1400. Upon request from customers we also deliver special designs with the help of our construction department.

Thus, along with the standard 90° swivel angle, we also supply actuators with different angles such as 120°, 135°, 180° and 3-position actuators (metering unit) as well as Scotch-Yoke actuators.

Our global sales market includes complete European area, Scandinavia, the Middle East, Africa. Asia and South America. Professional closeness to our customers is highly important for us. Benefit from our expertise!

You can send us an e-mail or call us at:

E-Mail: sales@airpower-gmbh.com
Phone: +49 2644 40697 0
Fax: +49 2644 40697 99




Technical specifications


Lug type		Standard version	By request
Nominal diameter		DN50 to DN1200, 2" to 48"	Other nominal sizes on request
Mounting between flanges	DN50 (2") to DN500 (20")	EN1092 -1 PN10, PN16, ANSI150	EN1092-1 PN6, ASME B16.1 CLASS125
	DN600 (24") and above	EN1092 - 1 PN10 Other standards by request	PN6, PN16, ANSI150
Standard pressure	DN50 (2") to DN200 (8")	16 bar (232 psi)	
	DN250 (10") and above	10 bar (145 psi)	
Maximum pressure	DN50 (2") to DN600 (24")	20 bar (290 psi)	
	DN700 (28") and above	16 bar (232 psi)	
Body		Ductile casting GGG40 (EN-JS-1030) (EN-GJS-400-15)	ductile cast iron GGG40.3 (EN-JS 1025) (EN)(EN-GJS-400-18-LT), Stainless steel 1.4408/AISI 316 A743 (CF8M), cast iron EN-GJL250 (GG25), Cast steel 1.0619/GP240GH (G-SC25)/A216 WCB
Disc		Stainless steel 1.4408	Stainless steel 1.4408(polished), Stainless steel 1.4404, Alu-bronze 2.0975, Hastelloy 2.4610, cast steel 1.0619, Stainless steel 1.4408/ ECTFE coated, Duplex 1.4462
The temperature of the medium is based on the possible sealing (elastomers)		EPDMH -30°C to +130°C NBR -20°C to +80°C	FKM -5°C to +150°C PTFE/FKM 0°C to +150°C Silicone -30°C to +135°C EPDMH/FDA -20°C to +130°C PTFE/EPDM 0°C to +130°C CSM/Hypalon -20°C to +100°C
Butterfly valves in double- and triple-eccentric version are also in our product range!			

Part description

Pos.-No.	Description
1	Body
2	Disc
3	Stem/Bolt
4	Seat (NBR, EPDM, Silicone, FKM, PTFE)
5	Bearing bush
6	V-Ring
7	Safety ring
8	Plug
9	Seal ring
10	Safety screws



Advantages/benefits of Series 24 DN50 (2") - DN1200 (48")



1	The stem safety ring is made of stainless steel and designed with a special geometry
2	The PTFE coated steel-bearing bushing ensures a high switching frequency
3	The V-type ring as an additional seal prevents leakage on the shaft
4	By vulcanizing the elastomer onto a support ring, the stability of the seat is ensured. Thus replacing the seat becomes very easy
5	The bolt is secured by a locking screw. An additional sealing ring ensures that the inside of the bolt is protected against dirt and liquids
6	The disc with the two-part shaft construction improves the C_v value of the butterfly valve and avoids turbulence. The shape of the disc edge ensures a low operating torque and extends the life of the butterfly valve
7	The special seat geometry guarantees a longer lifespan of the sealing. Automation with competitive prices. Ideal for vacuum applications. Easy mounting between two flanges

Torque values Series 24

Torque (Nm)

Series 24		Torque value at closed butterfly valve 16 bar (Nm)	Torque value at closed butterfly valve 10 bar (Nm)	Torque value at closed butterfly valve 6 bar (Nm)	Torque value at closed butterfly valve 3 bar (Nm)
DN	NPS				
DN50	2"	14,10	13,20	12,00	11,40
DN65	2 1/2"	14,80	13,60	12,50	12,10
DN80	3"	22,40	21,00	19,80	18,80
DN100	4"	41,53	37,80	35,00	32,20
DN125	5"	66,33	59,90	54,80	49,70
DN150	6"	103,80	93,20	84,20	74,60
DN200	8"	194,80	171,70	152,50	135,60
DN250	10"	332,00	288,10	249,70	214,60
DN300	12"	502,60	429,30	372,80	316,30
DN350	14"		622,20	542,30	470,40
DN400	16"		859,50	745,60	622,20
DN450	18"		1152,30	982,80	813,40
DN500	20"		1480,30	1254,00	1028,90
DN600	24"		2133,40	1830,10	1525,10
DN700	28"		3599,00	3059,00	2519,00
DN800	32"		4740,00	3981,00	3270,00
DN900	36"		7200,00	5976,00	5110,00
DN1000	40"		10500,00	8940,00	7350,00
DN1200	48"		15060,00	12800,00	10540,00

Note:

The table values refer to water, seawater, and hydrocarbon lubricants. Temperatures of 0°C to 80°C. Butterfly valves are to operate at least once a month. For other liquids and lubricating gases applications multiply the value by 1.25. For lubricant-free and dry media the value shall be multiplied by 1.3.

The operating torque value in the table is the sum of all friction and resistance values for the opening and closing of the disc at the specified pressure difference.

The effect of the dynamic torque is not considered in the table.

When sizing the actuator, the torque value in the table must be multiplied by 1.25.

The butterfly valve can be equipped with four different discs, which can be adapted to the differential pressure. The reference value is the pressure on the butterfly valve and the differential pressure. For example, with a butterfly valve size DN125 PN 16. If the differential pressure is 9 bar, a 75% disc should be used. The disc can be operated at 12 bar (75% of 16 bar).

Maximum permissible spindle torques in Nm for Series 24

Dimension		DN50 2"	DN65 2 1/2"	DN80 3"	DN100 4"	DN125 5"	DN150 6"	DN200 8"	DN250 10"	DN300 12"
torques- (Nm)	material SS420	73	73	112	178	178	446	446	1277	1277

Dimension		DN350 14"	DN400 16"	DN500 20"	DN600 24"	DN700 28"	DN800 32"	DN900 36"	DN1000 40"	DN1200 48"
torques (Nm)	material SS420	2400	2400	5216	9600	9600	24780	49926	49926	58098

Other materials available on request!

Flow values Series 24

Kv values (m³/h at 1 bar)

Series 24		Opening angle								
DN	NPS	10°	20°	30°	40°	50°	60°	70°	80°	90°
DN50	2"	0	0	5	11	21	41	77	101	120
DN65	2 1/2"	0	1	8	22	33	83	111	165	209
DN80	3"	0	6	18	38	53	94	174	279	388
DN100	4"	0	17	38	70	103	170	300	614	750
DN125	5"	0	24	61	115	170	288	494	978	1234
DN150	6"	0	34	88	174	263	434	751	1473	2044
DN200	8"	1	49	153	327	503	826	1406	2668	3924
DN250	10"	8	71	235	518	840	1423	2295	4211	6929
DN300	12"	18	91	324	775	1330	2133	3539	6373	11496
DN350	14"	36	100	486	1188	1788	2634	4147	7153	12558
DN400	16"	54	159	715	1674	2518	3467	5798	10858	15311
DN450	18"	88	271	967	1925	3108	4532	7249	13911	19857
DN500	20"	135	406	1266	2534	4009	6637	9403	16462	25403
DN600	24"	189	585	1874	3657	5283	8344	13224	24315	33315
DN700	28"	241	1211	2775	4829	7853	11096	17797	33332	43899
DN800	32"	343	2045	3848	6209	10955	15550	23452	43683	55441
DN900	36"	531	2614	5253	8189	14550	20702	32219	57256	69229
DN1000	40"	754	3338	6851	10917	18988	27563	42416	70630	82991
DN1200	48"	1071	4940	10746	18338	27935	43873	70523	110368	114824

Kv=m³ water per hour at 20°C and 1 bar of pressure loss.

c_v= 1.167 Kv


c_v= US gallons of water per minute at 60°F and 1 psi of pressure loss.

Weights Series 24



Dimension		Series 24 (Kg)
2"	DN50	3,10
2 1/2"	DN65	3,90
3"	DN80	4,90
4"	DN100	6,10
5"	DN125	9,80
6"	DN150	10,20
8"	DN200	17,60
10"	DN250	24,90
12"	DN300	36,50
14"	DN350	61,00
16"	DN400	90,00
18"	DN450	131,00
20"	DN500	150,00
24"	DN600	223,00
28"	DN700	340,00
32"	DN800	495,00
36"	DN900	650,00
40"	DN1000	750,00
48"	DN1200	1230,00

Lug type body dimensions Series 24 DN50 (2") to DN1200 (48") with bare shaft



Dimension	A	B	C	E/E1	D	F	G	n-Ød1	H	L1	L2
DN50	140	218	13,5	11*11	105	50	65	4-Ø7	11	43	46
DN65	152	232	13,5	11*11	124	50	65	4-Ø7	11	46	49,5
DN80	159	250	13,5	11*11	137	50	65	4-Ø7	12,5	46	49,5
DN100	178	285	13,5	14*14	170	50/70	90	4-Ø7/Ø9	12,5	52	55,5
DN125	190	320	17,5	14*14	197	70	90	4-Ø9	12,5	56	59
DN150	203	345	17,5	17*17	226	70	90	4-Ø9	13	56	59
DN200	238	405	24,5	17*17	279	70/102	125	4-Ø9/Ø11	14	60	64
DN250	268	475	24,5	22*22	336	102/125	152	4-Ø11/Ø13	15	68	72,5
DN300	306	538	24,5	22*22	396	102/125	152	4-Ø11/Ø13	16	78	81,5
DN350	340	633	30	27*27	446	125	175	4-Ø13	18	78	81,5
DN400	388	710	30	27*27	500	125/140	175	4-Ø13/Ø18	20	102	105
DN450	415	765	39	36*36	545	140	210	4-Ø18	22	114	118
DN500	441	825	49	36*36	600	140/165	210	4-Ø18/Ø21.5	23	127	130,5
DN600	505	950	49	46*46	718	165	210	4-Ø21.5	23	154	158
DN700	624	1129	58	55*55	910	254	300	8-Ø18	30	165	169
DN800	672	1248	58	55*55	1025	254	300	8-Ø18	32	190	195
DN900	720	1375	110	Ø90	1125	298	350	8-Ø22	34	203	208
DN1000	800	1518	120	Ø100	1255	298	350	8-Ø22	35	216	221
DN1200	941	1785	175	Ø120	1485	356	415	8-Ø32	35	254	260

Actuating units for butterfly valves

Aluminium hand lever with grid type RHA to DN200

- locking, adjustable in 10 positions
- lockable



Manual gear box type HGA from DN50 to DN300

- Ratio of between 37:1 to 45:1
- Torque of between 150 Nm to 750 Nm
- Gear of die cast aluminium



Manual gear box Type HGG from DN350 to DN1200

- Ratio of between 42:1 to 720:1
- Torque of between 497 Nm to 23786 Nm
- Housing made of cast iron and spheroidal graphite



Pneumatic Actuators from airpower

- Double acting
- Single acting
- Torque of between 2.4 Nm to 13.000 Nm
- Max. control pressure 8 bar

You can find more information about our drive on our website: www.airpower-gmbh.com




Electric actuator „auma“ or other

- Torques of between 10 Nm to 32000 Nm
- Terminal voltage: 3-ph AC

Volt	220	230	240	380	400	415	440	460	480	500
Hz	50	50	50	50	50	50	60	60	60	50




Lug type body dimensions Series 24 DN50 (2") to DN1200 (48") with manual gearbox




Dimension	A	B	D	F	H	L2	L3	L4	L5
DN50	140	218	105	100	11	139	99	80	48
DN65	152	232	124	100	11	139	99	80	48
DN80	159	250	137	100	12,5	139	99	80	48
DN100	178	285	170	100	12,5	139	99	80	48
DN125	190	320	197	120	12,5	165	115	100	54
DN150	203	345	226	120	13	165	115	100	54
DN200	238	405	279	300	14	293	220	146	71
DN250	268	475	336	300	15	293	220	146	71
DN300	306	538	396	300	16	293	220	146	71
DN350	340	633	446	400	18	291	208	138	72
DN400	388	710	500	400	20	377	277	184	81
DN450	415	765	545	500	22	395	287	210	81
DN500	441	825	600	500	23	483	357	248	91
DN600	505	950	718	500	23	540	382	313	93
DN700	624	1129	910	500	30	593	448	310	122
DN800	672	1248	1025	500	32	593	448	310	122
DN900	720	1375	1125	500	34	658	480	355	160
DN1000	800	1518	1255	500	35	658	480	355	160
DN1200	941	1785	1485	600	35	807	575	415	155

Lug type body dimensions Series 24 DN50 (2") to DN200 (8") with manual gearbox




Dimension	A	B	E	D	F	G	H	L2	L3
DN50	140	218	11*11	105	196	65	11	63	20,5
DN65	152	232	11*11	124	196	65	11	63	20,5
DN80	159	250	11*11	137	196	65	12,5	63	20,5
DN100	178	285	14*14	170	270	90	12,5	61	28,5
DN125	190	320	14*14	197	270	90	12,5	61	28,5
DN150	203	345	17*17	226	270	90	13	61	28,5
DN200	238	405	17*17	279	340	125	14	72	35

Pictures of Lug type series 24 with electric actuator



By request

Lug type body dimensions Series 24 with pneumatic actuator double acting type APD




Designed for minimum 6 bar control pressure

Dimension	A	B	D	G	H1	H2	L	L1	L2	APD
DN50	140	78	105	65	74	94	43	146	46	050
DN65	152	80	124	65	74	94	46	146	49,5	050
DN80	159	91	137	65	88	108	46	168	49,5	060
DN100	178	107	170	90	100	120	52	184	55,5	070
DN125	190	130	197	90	109	129	52	204	59	080
DN150	203	142	226	90	120	140	52	260	59	090
DN200	238	167	279	125	133	153	60	268	64	110
DN250	268	207	336	152	155	175	68	298	72,5	130
DN300	306	232	396	152	172	202	78	390	81,5	140
DN350	340	293	446	175	197	227	78	458	81,5	160
DN400	388	322	500	175	230	250	102	525	105	190
DN450	415	350	545	210	230	250	114	525	118	190
DN500	441	384	600	210	289	319	127	602	130,5	240
DN600	505	445	718	210	328	358	154	722	158	270
DN700	624	505	910	300	348	378	165	758	169	300
DN800	672	576	1025	300	408	438	190	888	195	350

DN900 - DN1200 upon request

Lug type body dimensions Series 24 with pneumatic actuator single acting type APS



Designed for minimum 6 bar control pressure

Dimension	A	B	D	G	H1	H2	L	L1	L2	APS
DN50	140	78	105	65	88	108	43	168	46	060
DN65	152	80	124	65	100	120	46	184	49,5	070
DN80	159	91	137	65	109	129	46	204	49,5	080
DN100	178	107	170	90	120	140	52	260	55,5	090
DN125	190	130	197	90	133	153	52	268	59	110
DN150	203	142	226	90	155	175	52	298	59	130
DN200	238	167	279	125	172	202	60	390	64	140
DN250	268	207	336	152	197	227	68	458	72,5	160
DN300	306	232	396	152	255	285	78	532	81,5	210
DN350	340	293	446	175	255	285	78	532	81,5	210
DN400	388	322	500	175	289	319	102	602	105	240
DN450	415	350	545	210	328	358	114	722	118	270
DN500	441	384	600	210	348	378	127	758	130,5	300
DN600	505	445	718	210	408	438	154	888	158	350
DN700	624	505	910	300	464	494	165	924	169	400

DN800 - DN1200 upon request



Assembly variants for actuator mounting „parallel to pipe“

Assembly version: H (double acting + single acting)

Safety position: spring closing, clockwise rotation „closed“

Standard: clockwise „CLOSED“
to DIN EN 15714-1



0° basic position



Assembly version: G (double acting + single acting)

Safety position: spring **opening**, clockwise


0° basic position



Assembly version: E (double acting + single acting)

Safety position: spring closing, **anti-clockwise**



0° basic position



Assembly version: F (double acting + single acting)

Safety position: spring **opening**, **anti-clockwise**

0° basic position



Actuator mounting „across the pipe“ on request.

Order code

Order example for resilient seated butterfly valve DN050 with bare shaft

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
	F	L	A	24	050	B	C	H	A	D	C	A	F05	V11	0
1 Type of acting F=bare shaft H= lever/gearbox P=pneum. Actuator, E=electric actuator															
2 Valve type W= Wafer, L= Lug															
3 A= Standard valve															
4 Valve series 23 = Wafer type, 24= Lug type, 35= Double Eccentric															
5 Nominal size of butterfly valve Nominal size: DN50-DN1200															
6 Body material B=Nodular casting EN-GJS-400-15 / EN-JS-1030 (GGG40)															
7 Disc material C=Stainless steel 1.4480/ ASTM 316 A743 / CF8M / AISI 316															
8 Body coating H= EPDMH, B= NBR Other materials on request!															
9 Stem material A= 1.4021/AISI420															
10 Pressure rate D= PN10/16															
11 Delta-p (Differential pressure) Δ C= 10 bar															
12 Construction length A= DIN EN 558-1 Range 20 (Series 23 and 24) K1															
13 Interface/square shaft F= DIN EN ISO 5211/ V= square shaft															
14 Assembly 0= no assembly Setup on request (presentation of actuating units on page 9)															

Service hotline for requests and information:


+49 2644 / 40697 0

Excerpt from the airpower product portfolio

Positioner



Solenoid valves



Limit switch box



Manual gearbox



pneumatic actuator



Pressure booster



Mounting brackets and couplings



airpower
europe gmbh
competence in actuators, valves and more



Auf der Hohl 7
D – 53547 Dattenberg

Tel. + 49 2644 / 406970
Fax. + 49 2644 / 4069799

info@airpower-gmbh.com



For Agent

www.airpower-gmbh.com